

1/10




FIG. 1



2/10




FIG.2
PRIOR ART

3/10




FIG.3
PRIOR ART




FIG.4
PRIOR ART

4/10




FIG.5A

5/10




FIG.5B




FIG.5C

6/10




FIG.6

7/10




FIG.7

8/10







FIG.8

9/10




REFERENCE, NORMAL DESIGN:



1010

ENHANCED DESIGN, TOP AND BOTTOM THERMAL FINGERS:



1020

TEMPERATURE (DEGC)
122.703
110.559
98.4154
86.2717
74.1279
61.9842
49.8405
37.6967
25.5533
13.4093

TEMPERATURE (DEGC)
104.203
94.1151
84.0288
73.9364
63.8501
53.7617
43.6734
33.5851
23.4867
13.4084



~ 15% THERMAL PERFORMANCE DECREASE IN PACKAGE LEVEL

FIG.9

10/10

1030



ENHANCED DESIGN, TOP AND BOTTOM THERMAL FINGERS + THERMAL VIAS:



~ 17% THERMAL PERFORMANCE DECREASE IN PACKAGE LEVEL

1040

ENHANCED DESIGN, TOP THERMAL FINGERS AND BOTTOM NET + VIAS:



~ 35% THERMAL PERFORMANCE DECREASE IN PACKAGE LEVEL

FIG. 10